



BLACK DIAMOND MATERIAL SCIENTECH PTE LTD

# TECHNICAL DATASHEET

<b>PRODUCT NAME:</b>	CARBON BLACK
<b>GRADE:</b>	PCnoir <sup>®</sup> 6315
<b>COLOR INDEX:</b>	PIGMENT BLACK 7
<b>CAS NO.:</b>	1333-86-4
<b>EINECS NO.:</b>	215-609-9

Properties	Data	Standard Regulation
Bet Surface Area (m <sup>2</sup> /g)	65±5	ASTM/D6556
DBP Absorption (Cc/100g)	70±3	ASTM/D2414
Tint Strength Vs Irb#3 (%)	90±5	ASTM/D3265
Loss Of Heating (Max%)	≤1.0	ISO1126
Ash Contents (Max%)	≤0.5	ASTM/D1506
Volatile Content (%)	≥1.0	DIN 53552
Residues On 45µm (Ppm Max%)	≤50	ISO 1437
pH	7.5±1	ASTM/D1512
Physical Form	Powder	Visual inspection

\***RECOMMEND APPLICATION:**Industrial Paint Color Matching, Architectural Paint Color Matching.etc

\***Packing:** 10kgs 3-ply paper bags of Powder form on wood pallet

\***Loading Volume of 1 X 20'FCL:** 7mt in 10kgs paper bags of Powder form

Note: This data is provided for reference only, detailing basic physicochemical properties of the product. Final performance must be tested and adjusted according to your intended application.

1 Raffles Place, One Raffles Place Mall, Singapore, 048616

+65 6978 8728

<http://www.bdms-carbonblack.com>

info@bdms-carbonblack.com

